

TECHNICAL DATA SHEET

Maxfilm

SYNTHETIC PENETRATING OIL AND MULTI-PURPOSE LUBRICANT

Royal Purple® Maxfilm® is a high film strength, multipurpose, synthetic lubricant / penetrant that excels in a wide array of applications. Maxfilm deeply penetrates, cleans and loosens rusted parts. Once applied, its solvent carrier evaporates and leaves a tenacious, thixotropic lubricating film on all metal surfaces, providing long-lasting protection against wear, rust and corrosion. Along with highly effective corrosion inhibitors and anti-wear agents, Maxfilm® contains Royal Purple's advanced and proprietary Synerlec® additive technology.

Synerlec® technology provides an exceptional film strength increase compared to any other comparable lubricant. The protection provided by Synerlec® dramatically reduces metal-to-metal contact and frictional wear, helping to extend power steering system component life and reduce parasitic power loss. Synerlec® also provides the lubricant with outstanding oxidation resistance to increase lubricant useful life and safely extend oil drains. The ionic attraction of Synerlec® to metal components provides unmatched wear protection, even in the absence of a full oil film.

RECOMMENDED USES

- PENETRATING OIL Loosening stuck and rusted parts such as nuts, bolts, locks, hinges, etc.
- MULTI-PURPOSE LUBRICANT Lubrication of power tools, hinges, chains, rollers, open gears, fishing tackle, lawn equipment, etc
- RUST/CORROSION PROTECTANT Preserves and protects parts in storage, machinery parts, wire ropes, etc., against corrosion

TECH TIP

For best results shake Maxfilm® well before each use and use the can in an upright position to maximize aerosol propellant life.

Typical Physical Properties		
Property	Test Method	
Viscosity @ 40°C, cSt	ASTM D445	7.6
Viscosity @ 100°C, cSt	ASTM D445	2.3
Viscosity Index	ASTM D2270	118
Flash Point, °C (°F)	ASTM D92	105 (221)
Pour Point, °C (°F)	ASTM D97	-51 (-60)
Rust Prevention, Dist. Water	ASTM D665A	PASS
Rust Prevention, Sea Water	ASTM D665B	PASS
4-Ball Wear, Scar, mm	ASTM D4172	0.4

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.