



Enduro-MP Grease

MULTI-PURPOSE EXTREME PRESSURE GREASE

Enduro-MP is a high performance, multi-service, calcium sulfonate complex grease. Its outstanding performance is achieved through a blend of high-quality base oils and additives, plus Royal Purple's unique, proprietary Synslide® additive technology. The superior Royal Purple grease formulation combined with a premium calcium sulfonate thickener provides unsurpassed protection against friction, wear and corrosion, and is inherently water resistant. Enduro-MP Grease significantly increases bearing life and equipment reliability, allowing bearings to run smoother, cooler, quieter, longer and more efficiently. Enduro-MP Grease satisfies a wide range of grease requirements and is recommended for bearings and general purpose use.

Royal Purple's Enduro-MP Grease gains its incredible performance from Synslide®. Synslide® is Royal Purple's unique, proprietary, noncorrosive EP additive technology. Premium-quality base oils and advanced additive chemistry enable Royal Purple to make superior lubricants, but it is Synslide® additive technology that gives Royal Purple's EP (extreme pressure) oils and greases their amazing performance advantages. Synslide® additive technology provides maximum protection under boundary lubrication conditions typically caused by heavy loads, slow operating speeds, and shock load conditions. This tenacious, slippery film significantly improves lubrication and reduces wear by increasing the oil film thickness and toughness, which helps to prevent metal-to-metal contact in gears and bearings.

Enduro-MP Grease is completely safe and non-corrosive to all ferrous alloys and yellow metals used in the manufacture of gears, bearings, and other rotating equipment components, including case-hardened gears that are easily pitted by conventional sulfur-phosphorus EP oils. Enduro-MP Grease is a superior multi-purpose EP grease that provides bearings the lubrication and protection needed to maximize equipment life and operational efficiency.

PERFORMANCE ADVANTAGES

- SUPERIOR HIGH-TEMPERATURE PERFORMANCE – Calcium sulfonate complex thickener provides a high dropping point and high-temperature stability to the grease
- OUTSTANDING WEAR PROTECTION - Synslide® additive technology and calcium sulfonate thickener drastically increase load carrying ability and imbues Enduro-MP with unmatched lubricant film strength, preventing metal-to-metal contact
- EXCEPTIONAL WATER RESISTANCE – Will not mix with water and has great resistance to water wash off
- REDUCED VIBRATION - The tough lubricating film cushions load and Synslide® micro-mends contacting bearing surfaces
- GREATER CORROSION PROTECTION – Advanced anti-corrosion additives along with the aluminum complex thickener provide unmatched corrosion protection for the lubricated components

Typical Physical Properties		
Property	Test Method	
NLGI Grade		2
Thickener Type		Ca Sulfonate
Worked Penetration	ASTM D217	265
Base Oil Viscosity @ 40°C, cSt	ASTM D445	136
Base Oil Viscosity @ 100°C, cSt	ASTM D445	10.9
Dropping Point, °C (°F)	ASTM D2265	338 (641)
Oil Separation Test, %	ASTM D1742	1.3
Water Washout, %	ASTM D1264	1.7
Rust Protection	ASTM D1743	Pass
Copper Corrosion, 24hr @ 100°C	ASTM D4084	1A
4-Ball EP Test, Weld Load, kg	ASTM D2596	620
4-Ball EP Test, Load Wear Index	ASTM D2596	105
Useful Temperature Range, °C (°F)	ASTM D5800	-40 to 177 (-40 to 350)

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

Distributed By Calumet Branded Products, LLC | 2780 Waterfront Pkwy, E. Dr., Suite 200 | Indianapolis, IN 46214 | Technical Services: 888-382-6300 | www.royalpurple.com

11/11/2024